

2.50mm .098" Center Wire to Board Connector



2520 Series

■ WAFER




- Part No.: 2520-WS-xxP

Specifications



- Electrical
- Voltage Rating: 250V AC,DC
- Current Rating: 2A
- Withstanding Voltage: 800V AC/ minute
- Insulation Resistance: 1,000M Ω Min
- Mates with: 2520-H-xxP

Material

- Circuits: 2~15
- Housing: Nylon 66, UL 94V-2
- Pin: Brass, Tin plated
- Temperature Range: -25~+85°C



PCB PATTREN LAYOUT



Ordering Information and Dimensions

CIRCUITS	PART NO.	DIMENSION	
		A	B
2	2520-WS-02P	2.50	7.50
3	2520-WS-03P	5.00	10.00
4	2520-WS-04P	7.50	12.50
5	2520-WS-05P	10.00	15.00
6	2520-WS-06P	12.50	17.50
7	2520-WS-07P	15.00	20.00
8	2520-WS-08P	17.50	22.50

CIRCUITS	PART NO.	DIMENSION	
		A	B
9	2520-WS-09P	20.00	25.00
10	2520-WS-10P	22.50	27.50
11	2520-WS-11P	25.00	30.00
12	2520-WS-12P	27.50	32.50
13	2520-WS-13P	30.00	35.00
14	2520-WS-14P	32.50	37.50
15	2520-WS-15P	35.00	40.00

2520 Series

■ WAFER




- Part No.: 2520-WR-xxP

Specifications



- Electrical
- Voltage Rating: 250V AC,DC
- Current Rating: 2A
- Withstanding Voltage: 800V AC/ minute
- Insulation Resistance: 1,000M Ω Min
- Mates with: 2520-H-xxP

Material

- Circuits: 2~15
- Housing: Nylon 66, UL 94V-2
- Pin: Brass, Tin plated
- Temperature Range: -25~+85°C



PCB PATTREN LAYOUT



Ordering Information and Dimensions

CIRCUITS	PART NO.	DIMENSION	
		A	B
2	2520-WR-02P	2.50	7.50
3	2520-WR-03P	5.00	10.00
4	2520-WR-04P	7.50	12.50
5	2520-WR-05P	10.00	15.00
6	2520-WR-06P	12.50	17.50
7	2520-WR-07P	15.00	20.00
8	2520-WR-08P	17.50	22.50

CIRCUITS	PART NO.	DIMENSION	
		A	B
9	2520-WR-09P	20.00	25.00
10	2520-WR-10P	22.50	27.50
11	2520-WR-11P	25.00	30.00
12	2520-WR-12P	27.50	32.50
13	2520-WR-13P	30.00	35.00
14	2520-WR-14P	32.50	37.50
15	2520-WR-15P	35.00	40.00