

2.54mm .100" Center Wire to Board Connector



7066 Series

■ WAFER




- Part No.: 7066-WS-xxP

Specifications



- Electrical
- Voltage Rating: 250V AC,DC
- Current Rating: 2.5A
- Withstanding Voltage: 600V AC/ minute
- Insulation Resistance: 1,000M Ω Min
- Mates with: 7066-H-xxP

Material

- Circuits: 2~12
- Housing: PBT, UL 94V-0
- Pin: Brass, Gold Flash
- Temperature Range: -25~+85°C



PCB PATTREN LAYOUT



Ordering Information and Dimensions

CIRCUITS	PART NO.	DIMENSION	
		A	B
2	7066-WS-02P	2.54	7.62
3	7066-WS-03P	5.08	10.16
4	7066-WS-04P	7.62	12.70
5	7066-WS-05P	10.16	15.24
6	7066-WS-06P	12.70	17.78
7	7066-WS-07P	15.24	20.32

CIRCUITS	PART NO.	DIMENSION	
		A	B
8	7066-WS-08P	17.78	22.86
9	7066-WS-09P	20.32	25.40
10	7066-WS-10P	22.86	27.94
11	7066-WS-11P	25.40	30.48
12	7066-WS-12P	27.94	33.02

7066 Series

■ WAFER




- Part No.: 7066-WR-xxP

Specifications



- Electrical
- Voltage Rating: 250V AC,DC
- Current Rating: 2.5A
- Withstanding Voltage: 600V AC/ minute
- Insulation Resistance: 1,000M Ω Min
- Mates with: 7066-H-xxP

Material

- Circuits: 2~12
- Housing: PBT, UL 94V-0
- Pin: Brass, Gold Flash
- Temperature Range: -25~+85°C



PCB PATTREN LAYOUT



Ordering Information and Dimensions

CIRCUITS	PART NO.	DIMENSION	
		A	B
2	7066-WR-02P	2.54	7.62
3	7066-WR-03P	5.08	10.16
4	7066-WR-04P	7.62	12.70
5	7066-WR-05P	10.16	15.24
6	7066-WR-06P	12.70	17.78
7	7066-WR-07P	15.24	20.32

CIRCUITS	PART NO.	DIMENSION	
		A	B
8	7066-WR-08P	17.78	22.86
9	7066-WR-09P	20.32	25.40
10	7066-WR-10P	22.86	27.94
11	7066-WR-11P	25.40	30.48
12	7066-WR-12P	27.94	33.02